

ARIZONA TILE

AEQUA SERIES



Aequa Tur



Aequa Castor



Aequa Cirrus



Aequa Nix



Aequa Silva



Aequa Tur

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
8" x 32" x 10mm	1.7216	6	10.3296	54	557.7984
8" x 32" x 10mm R11 Anti-Slip	1.7216	6	10.3296	54	557.7984
12" x 48" x 10mm	3.8736	4	15.4944	18	278.8992
Hex 2-1/2" x 2-1/2" x 10mm	0.82	10	8.2	45	369
4" x 32" SBN	N/A	4	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur. Please view actual material when making your selection, as the images on this page are only representative.

MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

COLORS

Aequa Castor
Aequa Cirrus
Aequa Nix
Aequa Silva
Aequa Tur

SIZES

8" x 32" x 10mm
*8" x 32" x 10mm R11 Anti-Slip
12" x 48" x 10mm
Hex 2-1/2" x 2-1/2" x 10mm

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

RECOMMENDED USES

Commercial & Residential
Interior
Exterior (R11 Anti-Slip Recommended)
Floor & Wall
Backsplashes
Countertops
Fireplaces
Tub Surrounds & Showers
Shower Floors (R11 & 2-1/2" x 2-1/2" hex only)
Vanities
Pools

TRIM

4" x 32" SBN

DYNAMIC C.O.F. WET: 0.65

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Aequa Series is a rectified color body porcelain. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of a reclaimed wood, this series provides the warmth of timeworn matter that has taken on new colors and nuances over time. Because this material is a porcelain product, minimal maintenance is required. Aequa Series is available in two sizes, 8" x 32" x 10mm and 12" x 48" x 10mm. The 8" x 32" x 10mm size is also available in R11 Anti-Slip finish, which makes it ideal for exterior applications. All sizes and finishes are available in five colors. Numerous patterns can be created with the available sizes. Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15", and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.