

# ARIZONA TILE

# AEQUA SERIES



Aequa Tur



Aequa Castor



Hex 2-1/2"



Aequa Cirrus



Hex 2-1/2"



Aequa Nix



Hex 2-1/2"



Aequa Silva



Hex 2-1/2"



Aequa Tur



Hex 2-1/2"

## PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

## MADE IN ITALY

## COLORS

Aequa Castor  
Aequa Cirrus  
Aequa Nix  
Aequa Silva  
Aequa Tur

## SIZES

8"x32"x10mm  
12"x48"x10mm  
Hex 2-1/2"x2-1/2"x10mm

## RECOMMENDED USES

Commercial & Residential  
Interior & Exterior  
Floor & Wall  
Backsplashes  
Countertops  
Fireplaces  
Tub Surrounds & Showers  
Vanities

## TRIM

4"x32" SBN

**DYNAMIC C.O.F. WET:** 0.65

**P.E.I. RATING:** 4

**FROSTPROOF:** Yes

The Aequa Series is a rectified color body porcelain. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of a reclaimed wood, this series provides the warmth of timeworn matter that has taken on new colors and nuances over time. Because this material is a porcelain product, minimal maintenance is required. Aequa Series is available in two sizes, 8"x32"x10mm and 12"x48"x10mm. It is available in five colors. Numerous patterns can be created with the available sizes. Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15", and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular tiles 18 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
8"x32"x10mm	1.7216	6	10.3296	54	557.7984
12"x48"x10mm	3.8736	4	15.4944	18	278.8992
Hex 2-1/2"x2-1/2"x10mm	0.82	10	8.2	45	369
4"x32" SBN	N/A	4	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur. Please view actual material when making your selection, as the images on this page are only representative.