



Aequa Nix



Aequa Castor



Aequa Cirrus



Aequa Nix



Aequa Silva



Aequa Tur



Hex 2-1/2"



Hex 2-1/2"



Hex 2-1/2"



Hex 2-1/2"



Hex 2-1/2"

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Aequa Castor
Aequa Cirrus
Aequa Nix
Aequa Silva
Aequa Tur

STOCKED SIZES

8 × 32 × 10mm
*8 × 32 × 10mm R11 Anti-Slip Finish
12 × 48 × 10mm
Hex 2-1/2 × 2-1/2 × 10mm

STOCKED TRIM

4 × 32 × 10mm SBN

SPECIAL ORDER SIZES

10-1/4 × 63 × 10mm
24 × 24 × 2cm
16 × 48 × 2cm

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com
Special Order: Please contact your Sales Representative or any Arizona Tile location for more details.

The Aequa Series is a rectified color body porcelain that is available in two finishes, including the R11 Anti-Slip Finish. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of a reclaimed wood, this series provides the warmth of timeworn matter that has taken on new colors and nuances over time. Because this material is a porcelain product, minimal maintenance is required. Aequa Series is stocked in two sizes, 8 × 32 × 10mm and 12 × 48 × 10mm. The 8 × 32 × 10mm size is also available in R11 Anti-Slip finish, which makes it ideal for exterior applications. All sizes and finishes are available in five colors. Numerous patterns can be created with the available sizes. Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15", and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

RECOMMENDED USES

Commercial
Residential
Interior Floor
Exterior Floor (R11 Anti-Slip Finish Only)
Countertops
Interior Wall
Exterior Cladding
Fireplaces
Showers
Steam Showers
**Shower Floors
Pool & Spa (waterline)

** 8 × 32 R11 Anti-Slip Finish and Hex 2-1/2 Inch Mosaic Only

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
8 × 32 × 10mm	1.7216	6	10.3296	54	557.7984
8 × 32 × 10mm R11 Anti-Slip	1.7216	6	10.3296	54	557.7984
12 × 48 × 10mm	3.8736	4	15.4944	18	278.8992
Hex 2-1/2 × 2-1/2 × 10mm	0.82	10	8.2	45	369
4 × 32 × 10mm SBN	N/A	4	N/A	N/A	N/A
10-1/4 × 63 × 10mm	4.4762	4	17.9048	18	322.2835
24 × 24 × 2cm	3.8736	2	7.7472	32	247.9104
16 × 48 × 2cm	5.1648	1	5.1648	48	247.9104

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.