

ARIZONA TILE

CALCUTTA SERIES



Calcutta Polished (cut to 6" x 24")



Calcutta Polished, Shimmer Abalone

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12" x 24" x 10mm Polished	1.9368	8	15.4944	40	619.7760
12" x 24" x 10mm Matte	1.9368	8	15.4944	40	619.7760
2" x 2" Mosaic Matte	0.9684	11	10.653	63	671.139
3" x 12" SBN Polished	N/A	40	N/A	60	2400 pieces
3" x 12" SBN Matte	N/A	40	N/A	60	2400 pieces

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.

PRODUCT TYPE
 Rectified Porcelain
 Digital Print Technology

FINISHES
 Polished
 Matte

STOCKED SIZES
 12" x 24" x 10mm
 Matte & Polished
 2" x 2" Mosaic Matte

STOCKED TRIM
 3" x 12" SBN
 Matte & Polished

RECOMMENDED USES
 Commercial (matte finish: floor & wall)
 Commercial (polished finish: wall only)
 Residential
 Interior Floor
 **Exterior Floor (matte finish only)
 Countertops
 Interior Wall
 Exterior Cladding
 Fireplaces
 Showers
 *Shower Floors
 Steam Showers
 Pool & Spa (waterline)

*2" x 2" Mosaic Matte only

P.E.I. RATING: 3 Polished 4 Matte
FROSTPROOF: Yes
DYNAMIC C.O.F. WET: 0.45 Matte
STATIC C.O.F. DRY: 0.89 Matte
STATIC C.O.F. WET: 0.68 Matte

**DCOF Rating is a measurement of a tiles frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Calcutta is a porcelain that is produced to emulate natural marble. Because this material is a porcelain product, minimal maintenance is required. To achieve the best range of veining, it is recommended to mix tiles from several boxes at a time during installation. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15", and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back