

ARIZONA TILE

ERAMOSA SERIES



Eramosa Clay



Eramosa Carbon



2 x 2 Basketweave



Stack



Eramosa Clay



2 x 2 Basketweave



Stack



Eramosa Ice



2 x 2 Basketweave



Stack



Eramosa Natural



2 x 2 Basketweave



Stack



Eramosa Sand



2 x 2 Basketweave



Stack

PRODUCT TYPE

Color Body Porcelain
Digital Print Technology

COLORS

Eramosa Carbon
Eramosa Clay
Eramosa Ice
Eramosa Natural
Eramosa Sand

STOCKED SIZES and FINISHES

6 x 36 x 10.6mm Matte Rectified
12 x 24 x 8.9mm Matte
12 x 24 x 8.9mm Polished Rectified
2 x 2 x 8.9mm Basketweave Matte
Stack Matte x 8.9mm

STOCKED TRIM

3 x 12 x 8.9mm SBN: Matte & Polished

RECOMMENDED USES

Commercial
Residential
Interior Floor
Countertops
Interior Wall
Exterior Cladding
Fireplaces
Showers
*Shower Floors
Steam Showers
Pool & Spa (waterline)

*2 x 2 Basketweave & Stack only

DYNAMIC C.O.F. WET: ≥ 0.42

(matte finish)

P.E.I. RATING: 4

FROSTPROOF: Yes

SPECIAL ORDER SIZE and FINISH

18 x 36 x 10.6mm Matte Rectified

Special Order Item: Please contact your sales representative or any Arizona Tile location for more details.

The Eramosa series is a color body porcelain that is produced to emulate a veined limestone. The unbelievable similarities between this product and actual limestone were made possible due to new, digital, inkjet technology. Eramosa is available in three sizes, plus a 2 x 2 Basketweave and Stack. Because this material is a porcelain product, minimal maintenance is required. Numerous patterns can be created with the available sizes. It is important to note that there is a slight difference in thickness between the 6 x 36 and 12 x 24 size. Piece to piece variation in shade or color are inherent in all fired clay products; therefore it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. For proper bonding, medium mortar should be used when installing tiles with a dimensional length greater than 15", and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required. Grout release is recommended for the polished finish, prior to grouting so grout powders do not fill pores in the tile surface, which can attract dirt when walked upon. This series is suitable for residential and commercial applications.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
6 x 36 x 10.6mm Matte Rectified	1.4046	6	8.4276	56	471.9456
6 x 36 x 10.6mm Matte Rectified	1.4046	6	8.4276	64	539.3664
12 x 24 Matte	1.9368	8	15.4944	32	495.8208
12 x 24 x 8.9mm Polished Rectified	1.8790	8	15.0320	32	481.0240
3 x 12 x 8.9mm SBN Matte & Polished	N/A	30	N/A	N/A	N/A
2 x 2 x 8.9mm Basketweave Matte	.8200	10	8.200	N/A	N/A
Stack Matte x 8.9mm	.9431	10	9.4310	45	N/A
18 x 36 x 10.6mm Matte Rectified	4.3590	3	13.077	31	405.3870

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.