


# ARIZONA TILE

# PIETRA ITALIA SERIES



Pietra Italia Grey 24 x 24




Pietra Italia White



Pietra Italia White  
2 x 2 Mosaic



Beige/White Stack



Pietra Italia Beige



Pietra Italia Beige  
2 x 2 Mosaic



Black/Grey Stack



Pietra Italia Grey



Pietra Italia Grey  
2 x 2 Mosaic




Pietra Italia Black



Pietra Italia Black  
2 x 2 Mosaic

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



## MADE IN ITALY

### PRODUCT TYPE

Rectified Through Body Porcelain

### COLORS

Pietra Italia Beige  
Pietra Italia Black  
Pietra Italia Grey  
Pietra Italia White

### STOCKED SIZES

12 x 24 x 10mm  
24 x 24 x 10mm  
24 x 48 x 10mm  
\*12 x 24 x 10mm R11 Anti-Slip  
\*24 x 48 x 10mm R11 Anti-Slip (Beige Only)

Beige/White Stack  
Black/Grey Stack  
0.93 sq ft/sheet

2 x 2 x 10mm Mosaic

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

### RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
\*\*Exterior Floor (R11 Anti-Slip Recommended)  
Countertops  
Interior Wall  
Exterior Cladding  
Fireplaces  
Showers  
Steam Showers  
Shower Floors (R11, 2 x 2 mosaic, and stacks only)  
Pool & Spa (waterline)

### STOCKED TRIM

3 x 12 x 10mm SBN

**D.C.O.F. WET:** ≥ 0.42

(Standard Finish)

**P.E.I. RATING:** 4

**FROSTPROOF:** Yes

\*\*DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized

Pietra Italia is a rectified through body porcelain that emulates a limestone. It provides a clean, natural stone look to any environment.

It is available in three sizes. Because this material is a porcelain product, minimal maintenance is required. Piece to piece variation in shade or color are inherent in all fired clay products; therefore it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15", and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 x 24 x 10mm	1.9368	8	15.4944	32	495.8208
12 x 24 x 10mm R11 Anti-Slip Finish	1.9368	8	15.4944	32	495.8208
24 x 24 x 10mm	3.8736	4	15.4944	32	495.8208
24 x 48 x 10mm	7.7472	2	15.4944	36	557.7984
24 x 48 x 10mm R11 Anti-Slip Finish (Beige Only)	7.7472	2	15.4944	36	557.7984
Beige/White Stack Black/Grey Stack	0.93 sq ft/sheet	N/A	N/A	N/A	N/A
2 x 2 x 10mm Mosaic	0.9588	10 sheets	9.588	45	431.46

**DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.**

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.