

ARIZONA TILE

PORTA NUOVA SERIES



PN-Quercia



PN-Ciliegio



PN-Ebano



PN-Frassino



PN-Noce



PN-Quercia



PN-Rovere

MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

COLORS

PN-Ciliegio
PN-Ebano
PN-Frassino
PN-Noce
PN-Quercia
PN-Rovere

STOCKED SIZE

6-1/2 × 40 × 10mm

RECOMMENDED USES

Commercial
Residential
Interior Floor
Countertops
Interior Wall
Exterior Cladding
Fireplaces
Showers
Steam Showers
Pool & Spa (waterline)

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

The Porta Nuova Series is a rectified color body porcelain. Inspired by the rich tones of natural wood, this series has an organic look and offers a warm, enduring appeal. It is available in six neutral, on-trend colors and provides an inviting aesthetic that is available for residential and commercial installations. Because this material is a porcelain product, maintenance risks involved with actual wood flooring are eliminated.

There will be noticeable variations in color and movement between pieces. Therefore, it is important and recommended that a range of this product be viewed before finalizing a purchase. This series is suitable for residential and commercial applications. For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15" and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
6-1/2 × 40 × 10mm	1.7216	6	10.3296	48	495.8208
6-1/2 × 40 × 10mm	1.7216	6	10.3296	54	557.7984

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.