

ARIZONA TILE

STAGE SERIES



Stage Grey and Stage Grey Boss



Stage Blue

Stage Grey


Stage Red



Stage Blue Boss
(12 x 24 only)

Stage Grey Boss
(12 x 24 only)

Stage Red Boss
(12 x 24 only)



Stage Blue
2 x 2 Mosaic



Stage Grey
2 x 2 Mosaic



Stage Red
2 x 2 Mosaic



Stage Blue
1 x 12 Stack



Stage Grey
1 x 12 Stack



Stage Red
1 x 12 Stack

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



MADE IN ITALY

PRODUCT TYPE

Rectified Glazed Porcelain

COLORS

Stage Blue
Stage Grey
Stage Red

STOCKED SIZES

12 x 24 x 9mm
12 x 24 x 9mm Boss
24 x 24 x 9mm
*1 x 12 x 9mm Stack
*2 x 2 x 9mm Mosaic

*Minimal chipping on the edge of the tile is to be expected in mesh-mounted products

SPECIAL ORDER SIZES

24 x 48 x 9mm
24 x 24 x 9mm Boss
24 x 48 x 9mm Boss

RECOMMENDED USES

Commercial
Residential
Interior Floor
Countertops
Interior Wall
Exterior Cladding
Fireplaces
Showers
**Shower Floors
Steam Showers
Pool & Spa (waterline)

**2 x 2 Mosaic and 1 x 12 only

STOCKED TRIM

3 x 12 x 9mm SBN

D.C.O.F. WET: ≥ 0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

Special Order Item:

Please contact your sales representative or any Arizona Tile location for more details.

The Stage Series is a Rectified Glazed Porcelain. It emulates structured, dulled metal that is very distinctive and adds a strong statement to any environment. The Boss version is reminiscent of the anti-slip finishes of stage construction materials. Digital print technology makes this unique look possible. Because this material is a porcelain product, minimal maintenance is required. Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15" and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.



Stage Red & Stage Red Boss



Stage Grey & Stage Grey Boss

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 x 24 x 9mm	1.9368	5	9.6840	56	542.3040
12 x 24 x 9mm Boss	1.9368	5	9.6840	56	542.3040
24 x 24 x 9mm	3.8736	3	11.6208	40	464.8320
1 x 12 x 9mm Stack	0.9588	10 sheets	9.588	45	450 sheets
2 x 2 x 9mm Mosaic	0.9588	10 sheets	9.588	45	431.46
3 x 12 x 9mm SBN	N/A	30	N/A	N/A	N/A
24 x 48 x 9mm	7.7472	2	15.4944	24	371.8656
24 x 24 x 9mm Boss	3.8736	3	11.6208	40	464.8320
24 x 48 x 9mm Boss	7.7472	2	15.4944	24	371.8656

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.