



Ardesia Grey




Ardesia Ash 12 x 24



2 x 2 Mosaic Mesh



Ardesia Black 12 x 24



2 x 2 Mosaic Mesh



Ardesia Grey 12 x 24



2 x 2 Mosaic Mesh



Ardesia Light 12 x 24



2 x 2 Mosaic Mesh



### PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

### STOCKED COLORS

Ardesia Ash  
Ardesia Black  
Ardesia Grey  
Ardesia Light

### STOCKED SIZES

12 x 24 x 8.2mm  
12 x 24 x 10mm  
24 x 48 x 8.2mm  
24 x 48 x 10mm  
\*24 x 48 x 8.2mm R11 Anti-Slip Finish  
\*24 x 48 x 10mm R11 Anti-Slip Finish  
2 x 2 x 10mm Mosaic Mesh

Contact your local Arizona Tile for thickness availability.

### STOCKED TRIM

3 x 12 x 10mm SBN

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

### RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
\*Exterior Floor  
Interior Wall  
Exterior Cladding  
Fireplaces  
Shower Walls  
\*\*Shower Floors  
Steam Showers  
Pool & Spa  
\*24 x 48 R11 Anti-Slip Finish Only  
\*\*24 x 48 R11 Anti-Slip Finish and 2 x 2 Mosaic Mesh Only

DYNAMIC C.O.F. WET:  $\geq 0.42$

P.E.I. RATING: 3 (Black)

4 (Ash, Grey, & Light)

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Ardesia series is an American-made rectified color body porcelain tile that is available in four colors. Created using digital print technology, Ardesia has the look of natural stone which makes it very versatile as it compliments both contemporary and traditional spaces.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. Because this material is a porcelain product, minimal maintenance is required.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS  
 $\geq 15\%$  PRE-CONSUMER  
RECYCLED CONTENT**

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 x 24 x 8.2mm & 10mm	2	6	12	48	576
24 x 48 x 8.2mm	8	2	16	36	576
24 x 48 x 10mm	8	2	16	32	512
24 x 48 x 8.2mm R11 Anti-Slip Finish	8	2	16	36	576
24 x 48 x 10mm R11 Anti-Slip Finish	8	2	16	32	512
2 x 2 x 10mm Mosaic Mesh	0.9588	10 sheets	9.588	45	431.46
3 x 12 x 10mm Surface Bullnose (SBN)	N/A	30	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.