



Futura Greige



PRODUCT TYPE
 Rectified Color Body Porcelain
 †Glazed Porcelain
 Digital Print Technology

STOCKED COLORS
 Futura Beige
 Futura Greige
 Futura Ivory
 Futura Silver

RECOMMENDED USES

- Commercial
- Residential
- Interior Floor
- *Exterior Floor
- Interior Wall
- Exterior Cladding
- Fireplaces
- Shower Walls
- **Shower Floors
- Steam Showers
- Pool & Spa

*24 x 48 R11 Anti-Slip Finish Only
 **2 x 2 Mosaic Mesh and R11 Anti-Slip Finish Only

STOCKED SIZES

- 12 x 24
- †*24 x 24 x 2cm
 Paver R11 Anti-Slip Finish
- 24 x 48
 *24 x 48 R11 Anti-Slip Finish
- 2 x 2 Mosaic Mesh

PAVER RECOMMENDED USES

- †Commercial
- †Residential
- †Exterior Floor
- †Pool & Spa

STOCKED TRIM

- 3 x 12 SBN

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

DCOF rating is a measurement of a tile's frictional resistance. The listed result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Futura series is an American-made rectified color body porcelain offered in four neutral colors. Created using digital print technology, Futura has the look of a limestone which makes it very versatile as it compliments both contemporary and traditional spaces. Now available in a 24 x 24 2cm paver R11 Anti-Slip Finish for additional exterior design possibilities.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. Because this material is a porcelain product, minimal maintenance is required.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.



Futura Beige



2 x 2 Mosaic Mesh



Futura Greige



2 x 2 Mosaic Mesh



Futura Ivory



2 x 2 Mosaic Mesh



Futura Silver



2 x 2 Mosaic Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
 ≥30%PRE-CONSUMER
 RECYCLED CONTENT**

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 05/01/24