# ARIZONA TILE

## **REFLEXION SERIES**



Reflexion Bright & Titanium



Reflexion Bright



Reflexion Mercury



Reflexion Night




Reflexion Titanium



2 × 2 Mosaic Mesh



2 × 2 Mosaic Mesh



2 × 2 Mosaic Mesh



2 × 2 Mosaic Mesh



#### PRODUCT TYPE

Color Body Porcelain
Digital Print Technology

#### STOCKED COLORS

Reflexion Bright Reflexion Mercury Reflexion Night Reflexion Titanium

#### STOCKED SIZES

 $12 \times 24 \times 9$ mm  $24 \times 48 \times 9$ mm Rectified  $2 \times 2 \times 9$ mm Mesh Mosaic

#### STOCKED TRIM

 $3 \times 12 \times 9$ mm SBN

### **RECOMMENDED USES**

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
\*Shower Floors
Steam Showers
Pool & Spa
\*2 × 2 Mosaic Mesh Only

**DYNAMIC C.O.F. WET**: ≥0.42

P.E.I RATING: 4
FROSTPROOF: Yes

The Reflexion series has the shimmering look of metal, with its infinite transformations of light and reflections is combined with the solid mood of concrete which adds an urban feeling and a modern taste to every environment. Because this material is a porcelain product, minimal maintenance is required.

There can be noticeable variances between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. This series is suitable for residential and commercial projects.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required. This series is suitable for residential and commercial applications.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.

		-	
		l	
		l	
	$\leftrightarrow$		
	≤33% OFFSET		
	OFFSET		

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 × 24 × 9mm	1.9375	7	13.5625	40	542.5
24 × 48 × 9mm	7.75	2	15.5	35	542.5
2 × 2 × 9mm Mosaic Mesh	0.9588	10	9.588	45	431.46
3 × 12 × 9mm Surface Bullnose (SBN)	N/A	N/A	N/A	N/A	N/A