

# ARIZONA TILE

# RESIDE USA SERIES



Reside Ash USA 24 x 48 R11 Anti-Slip Finish



Reside Ash USA



Straight Stack  
1 x 12 Mesh



2 x 2 Mosaic Mesh



Reside Beige USA



Straight Stack  
1 x 12 Mesh




2 x 2 Mosaic Mesh



Reside Black USA




Straight Stack  
1 x 12 Mesh



2 x 2 Mosaic Mesh



Reside Brown USA



Straight Stack  
1 x 12 Mesh



2 x 2 Mosaic Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



## PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

## STOCKED COLORS

Reside Ash USA  
Reside Beige USA  
Reside Black USA  
Reside Brown USA

## STOCKED FINISHES

Matte  
R11 Anti-Slip Finish

## STOCKED SIZES

12 x 24 x 8mm  
24 x 24 x 8mm  
24 x 48 x 8mm  
\*24 x 48 x 8mm R11 Anti-Slip Finish  
2 x 2 x 8mm Mosaic Mesh  
Straight Stack 1 x 12 Mesh

## STOCKED TRIM

3 x 12 x 8mm SBN

## RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
\*Exterior Floor  
Interior Wall  
Exterior Cladding  
Fireplaces  
Shower Walls  
\*\*Shower Floors  
Steam Showers  
Pool & Spa

\* 24 x 48 R11 Anti-Slip Finish Only  
\*\* 2 x 2 Mosaic Mesh, Straight Stack 1 x 12 and R11 Anti-Slip Finish Only

**DYNAMIC C.O.F. WET:** ≥0.42

**P.E.I. RATING:** 4

**FROSTPROOF:** Yes

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish.

The Reside USA Series is a rectified color body porcelain. Inspired by the rich textures of commercial textiles, this series has a clean look and offers a simplistic, modern appeal. It is available in four neutral, on-trend colors and provides an industrial and commercial aesthetic that is available for residential installations as well.

Piece to piece variation in shade or color are inherent in all fired clay products: therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial applications.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 x 24 x 8mm	1.9375	8	15.5	32	496
24 x 24 x 8mm	3.8750	4	15.5	32	496
24 x 48 x 8mm	7.75	2	15.5	35	542.5
24 x 48 x 8mm	7.75	4	31	20	620
24 x 48 x 8mm R11 Anti-Slip Finish	7.75	2	15.5	35	542.5
24 x 48 x 8mm R11 Anti-Slip Finish	7.75	4	31	20	620
2 x 2 x 8mm Mosaic Mesh	0.9588	10	9.588	45	431.46
Straight Stack 1 x 12 Mesh	0.9555	10	9.555	45	429.975
3 x 12 x 8mm Surface Bullnose (SBN)	N/A	30	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.

[www.arizonatile.com](http://www.arizonatile.com)