ARIZONA TILE

CITYLIFE SERIES



CityLife Ash 36 × 36





2 × 2 Mosaic Mesh

2 × 2 Mosaic Mesh

CityLife Ash



CityLife Beige




CityLife Sand



CityLife Tin



2 × 2 Mosaic Mesh



2 × 2 Mosaic Mesh

MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain Digital Print Technology

STOCKED COLORS

CityLife Ash CityLife Beige CityLife Sand CityLife Tin

STOCKED SIZES

12 × 24 36 × 36 24 × 48 2 × 2 Mosaic Mesh

Mosaic Mesh

STOCKED TRIM 3 × 12 SBN

RECOMMENDED USES

Commercial Residential Interior Floor Interior Wall Exterior Cladding Fireplaces Shower Walls *Shower Floors Steam Showers Pool & Spa *2 × 2 Mosaic Mesh Only

DYNAMIC C.O.F. WET: ≥0.42 P.E.I. RATING: 4 FROSTPROOF: Yes

The CityLife series is an Italian-made rectified color body porcelain tile available in four neutral colors and four sizes. Created using digital print technology, CityLife offers a look that is versatile and well suited to a contemporary furnishing style.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. Because this material is a porcelain product, minimal maintenance is required.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

> When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.

S33% OFFSET

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application. Please view actual material when making your selection, as the images on this page are only representative. Revised 05/01/24 WWW.arizonatile.com

PRODUCT CONTAINS ≥20% PRE-CONSUMER

RECYCLED CONTENT