



Vincen White



Vincen Bone



2 x 2 Mosaic Mesh



Vincen Lido



2 x 2 Mosaic Mesh



Vincen White



2 x 2 Mosaic Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 04/28/26

MADE IN SPAIN

PRODUCT TYPE

Rectified Glazed Porcelain
 †Glazed Porcelain
 Digital Print Technology

STOCKED COLORS

Vincen Bone
 Vincen Lido
 Vincen White

STOCKED FINISHES

Matte
 *R11 Finish

STOCKED SIZES

12 x 24
 †*24 x 36 x 2cm Paver R11 Finish
 24 x 48
 *24 x 48 R11 Finish
 2 x 2 Mosaic Mesh **Coming Soon**

STOCKED TRIMS **Coming Soon**

3 x 12 Surface Bullnose
 †Easy Edge 13 x 24 x 2cm Coping

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

The Outer Limits® Collection includes products designed for outdoor living, featuring slip-resistant porcelain tiles, and countertop materials ideal for outdoor kitchens and exposed environments. Please confirm which exterior surface(s) a product is recommended for in the Products section of our website.

The Vincen series is glazed porcelain tile made in Spain. This design is reminiscent of a limestone which offers an overall even tone but upon closer look the design is rich with inclusions of fossilized organic materials such as shells and plants. This series also offers a paver for exterior use as well as coping for pool installations. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial application.

The Easy Edge 13 x 24 x 2cm Coping (nominal size; actual coping size: 33.6cm x 59.7cm, approximately 13.2" x 23.5") is glazed and kiln-fired on both the top surface and the exposed front edge, providing a clean, finished look. It is designed for use in pool areas and on stair treads. A functional drip groove is incorporated into the underside of the coping edge. This small, recessed channel helps prevent water from running back underneath the coping by directing it to drip away cleanly — reducing the risk of staining, efflorescence, or damage to vertical surfaces below. The 24" (nominal) front edge aligns with the 24" rectified dimension of the paver in this series, ensuring a seamless visual transition.

Please note that variation in shade, tone, and surface finish is an inherent characteristic of all fired clay products, including differences between pavers and copings. Additionally the pavers and coping are produced in separate manufacturing runs, so shade variation is expected; all material must be inspected and approved prior to installation. For custom sizes or multiple-sided edges, please contact your Sales Representative or any Arizona Tile location.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. Please note, for pavers, a minimum grout spacing of 1/8" or 3mm is recommended. For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

RECOMMENDED USES

Commercial
 Residential
 Interior Floor
 *Exterior Floor
 Interior Wall
 Exterior Cladding
 Fireplaces
 Shower Walls
 **Shower Floors
 Steam Showers
 Pool & Spa
 *24 x 48 R11 Finish & 24 x 36 Paver R11 Finish Only
 **2 x 2 Mosaic Mesh & 24 x 48 R11 Finish Only

PAVER RECOMMENDED USES

†Commercial
 †Residential
 †Exterior Floor

D.C.O.F. WET: ≥0.42

P.E.I. RATING: 4 (tile), 5 (coping)

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Finish.