



PRODUCT TYPE

Quartzite

ORIGIN

Brazil

STOCKED FINISH

Satin

RECOMMENDED USES

Commercial

Residential

Interior Countertops

Interior Wall

Fireplaces

Shower Walls

STOCKED SIZES

3/4" (2cm slab)

1-1/4" (3cm slab)

Mont Blanc Satin is quarried from a bedrock quarry in Brazil. It resembles marble in appearance, but is much harder and more durable. Because of this, it can be used for kitchen countertops without having the scratching and etching issues experienced with marble. Mont Blanc Satin has a creamy white background with grey and taupe veining. It is possible for some slabs to have areas that are stark white, or have light oxidation. During the brushing process, an epoxy resin is applied to the surface of the stone to fill in any natural pits, cracks or fissures that may exist. It is possible for some of the more minute pits that are too small to effectively hold the resin, to reopen during other finishing stages. However, this does not affect the durability, maintenance or beauty of the stone. Due to the qualities of the stone, the slabs are book-matched, meaning slab one and slab two will be cut and brushed to create a mirror image of each other. These are then kept in sequence, which allows for a consistent flow in pattern. Finally, a mesh backing is adhered to the back of the stone to ensure safety while handling and fabricating the slab.

As a natural stone product, it is recommended that this be sealed to extend its longevity. Natural stone may absorb moisture during fabrication and from installation materials. Therefore, it is recommended that sealing should be done after the stone has fully dried to ensure proper sealer absorption, and prior to consumer use. Drying time will vary depending on the stone, as well as the temperature and humidity level. Quartzite has a more open structure and therefore needs a sealer that is designed to penetrate properly to ensure that the stone is sealed. After sealing, allow it to cure completely. Arizona Tile suggests using 3-5 coats of solvent-based impregnating sealer for the initial sealing and applying 1 coat of sealer every 6 months moving forward. It's also recommended to seal all cut edges, on-site at the time of installation. This will help to minimize water and oils from penetrating into the stone around sinks, faucet holes, ovens and any seams.