




Canyon Grey



Canyon Black




Straight Stack
1 x 24 Mesh




Hex 16 x 18 Mesh




Canyon Brown




Straight Stack
1 x 24 Mesh



Hex 16 x 18 Mesh



Canyon Grey



Straight Stack
1 x 24 Mesh



Hex 16 x 18 Mesh



Canyon Ivory




Straight Stack
1 x 24 Mesh



Hex 16 x 18 Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 05/07/24

MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Canyon Black
Canyon Brown
Canyon Grey
Canyon Ivory

STOCKED SIZES

12 x 24
24 x 24
24 x 48
*24 x 48 R11 Anti-Slip Finish
2 x 2 Mosaic Mesh
Straight Stack 1 x 24 Mesh
Hex 16 x 18 Mesh

STOCKED TRIM

3 x 12 SBN

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

RECOMMENDED USES

Commercial
Residential
Interior Floor
*Exterior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
**Shower Floors
Steam Showers
Pool & Spa

*24 x 48 R11 Anti-Slip Finish Only

**2 x 2 Mosaic Mesh, Straight Stack 1 x 24 Mesh and 24 x 48 R11 Anti-Slip Finish Only

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 3 (Black, Brown, Grey)
5 (Ivory)

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Canyon series is an Italian-made rectified color body porcelain that is available in two finishes, including the R11 Anti-Slip Finish. Created using digital print technology, this durable porcelain tile has a variety of tones that mimics the look of slate. This product is a truthful representation of a natural slate, with all its natural traits, including shade variation, as well as structural and saw-cut effects.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. Because this material is a porcelain product, minimal maintenance is required.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.