

ARIZONA TILE

BIO ATTITUDE SERIES



BA-Almond



Straight Stack
1 × 24 Mesh



Hex 16 × 18 Mesh



BA-Amber



Straight Stack
1 × 24 Mesh



Hex 16 × 18 Mesh



BA-Barrel



Straight Stack
1 × 24 Mesh



Hex 16 × 18 Mesh



BA-Cortex



Straight Stack
1 × 24 Mesh



Hex 16 × 18 Mesh



BA-Cotton



Straight Stack
1 × 24 Mesh



Hex 16 × 18 Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



MADE IN ITALY

PRODUCT TYPE

Rectified Glazed Porcelain
Digital Print Technology

STOCKED COLORS

BA-Almond
BA-Amber
BA-Barrel
BA-Cortex
BA-Cotton

STOCKED SIZES

8 × 48
Straight Stack 1 × 24 Mesh
Hex 16 × 18 Mesh

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
Shower Floors
Steam Showers
Pool & Spa

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

The Bio Attitude series is a rectified glazed porcelain that captures the truest essence of oak, making us rediscover the rustic beauty of nature. An added benefit is that Bio Attitude features PROTECT® technology, which works continuously to eliminate up to 99.9% of bacteria. PROTECT® surfaces have been developed with Microban®, a proven antimicrobial product protection technology developed by the world leader in the sector. Integrated during the manufacturing stage, Microban® helps fight the growth of degrading bacteria on the surface of the tile for its expected lifetime. The result is a surface that stays cleaner and fresher in between cleans. It is also inherently more durable and unalterable by climate conditions. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial applications.

There can be noticeable variance between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

**PRODUCT CONTAINS
≥40% PRE-CONSUMER
RECYCLED CONTENT**

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 10/28/24

www.arizonatile.com