



Intense Beige Trait 24 x 48



Intense Beige



2 x 2 Mosaic Mesh



Intense Clair



2 x 2 Mosaic Mesh



Intense Perle



2 x 2 Mosaic Mesh




Intense Toffee



2 x 2 Mosaic Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS  
≤40%PRE-CONSUMER  
RECYCLED CONTENT**

For packaging information, please contact your local Arizona Tile.

**DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.**

Please view actual material when making your selection, as the images on this page are only representative.

Revised 02/03/25

## MADE IN ITALY

### PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

### STOCKED COLORS

Intense Beige  
Intense Clair  
Intense Perle  
Intense Toffee

### STOCKED FINISHES

Matte  
R11 Anti-Slip Finish

### STOCKED SIZES

12 x 24  
24 x 24  
24 x 48  
\*24 x 48 R11 Anti-Slip Finish  
24 x 48 Trait  
2 x 2 Mosaic Mesh  
Mixed Chevron Mesh [Coming Soon](#)  
Mixed Hex 4" Mesh [Coming Soon](#)  
Mixed Straight Stack 1 x 12 Mesh [Coming Soon](#)

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

### RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
\*Exterior Floor  
Interior Wall  
Exterior Cladding  
Fireplaces  
Shower Walls  
\*\*Shower Floors  
Steam Showers  
Pool & Spa  
\*24 x 48 R11 Anti-Slip Finish Only  
\*\*2 x 2 Mosaic Mesh, Mixed 4" Hex Mesh, Mixed Straight Stack 1 x 12 Mesh and 24 x 48 R11 Anti-Slip Finish Only

### STOCKED TRIM

3 x 12 SBN [Coming Soon](#)

**DYNAMIC C.O.F. WET: ≥0.42**

**P.E.I. RATING: 4**

**FROSTPROOF: Yes**

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Intense series is an Italian made porcelain. Inspired by sedimentary limestone, this series faithfully reproduces the granules and micro-inclusions of fossils that are typical of this stone. The 24 x 48 size includes a Trait texture that recreates the effect of chiseled stone through a processing technique that uses engraving to give the entire surface a more decorative look, yet can still be used on floors. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial application.

Intense features PROTECT<sup>®</sup> technology, which makes it easy to sanitize and eliminates up to 99.9% of bacteria. Besides being beautiful and remarkably resistant, PROTECT<sup>®</sup> surfaces have been crafted with Microban<sup>®</sup>, a proven antimicrobial product protection technology developed by the world leader in the sector. Integrated during the manufacturing stage, Microban<sup>®</sup> helps fight the growth of degrading bacteria on the surface of the tile for its expected lifetime. The result is a surface that stays cleaner and fresher in between cleans. It is also inherently more durable and unalterable by climate conditions.

When mixing sizes within a series, shade, texture and calibration differences should be expected. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.