



Invictus Cross Cut Beige




Invictus Beige Cross Cut



2 x 2 Mosaic Mesh



Invictus Ivory Cross Cut



2 x 2 Mosaic Mesh



Invictus Pearl Cross Cut



2 x 2 Mosaic Mesh




Invictus White Cross Cut



2 x 2 Mosaic Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
>20%PRE-CONSUMER
RECYCLED CONTENT**

MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Invictus Beige Cross Cut
Invictus Ivory Cross Cut
Invictus Pearl Cross Cut
Invictus White Cross Cut

STOCKED FINISHES

Matte (M)
Polished (P)
R11 Anti-Slip Finish

STOCKED SIZES

12 x 24 (M, P)
24 x 24 (M, P)
24 x 48 (M, P)
*24 x 48 R11 Anti-Slip Finish
2 x 2 Mosaic Mesh (M)

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

RECOMMENDED USES

Commercial
Residential
Interior Floor
*Exterior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
**Shower Floors
Steam Showers
Pool & Spa

*24 x 48 R11 Anti-Slip Finish Only

**Matte 2 x 2 Mosaic Mesh and
24 x 48 R11 Anti-Slip Finish Only

STOCKED TRIM

3 x 12 SBN (M, P) [Coming Soon](#)

DYNAMIC C.O.F. WET: ≥0.42 (M)

P.E.I. RATING: 4 (P), 5 (M, R11)

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Invictus Cross Cut series is an Italian-made rectified color body porcelain. Created using digital print technology, the Invictus Cross Cut porcelain tile design resembles a cross cut travertine. You have several finish options with the desirable 24 x 48 large format tile size including matte, polished and R11 Anti-Slip Finish for exterior flooring. See Invictus Vein Cut series for additional stocked coordinating items. This series is suitable for residential and commercial applications. Because this material is a porcelain product, minimal maintenance is required.

There can be noticeable variances between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected.

Grout release is recommended for the polished finish, prior to grouting so grout powders do not fill pores in the tile surface, which can attract dirt when walked upon. It is recommended to use a coordinating grout color for all polished porcelain, contrasting grout colors are not recommended. For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 02/03/25