



Invictus Beige Vein Cut



2 x 2 Mosaic Mesh



4 Inch Hex



Large Chevron



Invictus Ivory Vein Cut



2 x 2 Mosaic Mesh



4 Inch Hex



Large Chevron



Invictus Pearl Vein Cut



2 x 2 Mosaic Mesh



4 Inch Hex



Large Chevron



Invictus White Vein Cut



2 x 2 Mosaic Mesh



4 Inch Hex



Large Chevron

## MADE IN ITALY

### PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

### STOCKED COLORS

Invictus Beige Vein Cut  
Invictus Ivory Vein Cut  
Invictus Pearl Vein Cut  
Invictus White Vein Cut

### STOCKED FINISHES

Matte (M)  
Polished (P)  
R11 Anti-Slip Finish

### STOCKED SIZES

12 x 24 (M, P)  
24 x 48 (M, P)  
\*24 x 48 R11 Anti-Slip Finish  
24 x 48 Rigato (M)  
2 x 2 Mosaic Mesh (M) **Coming Soon**  
4 Inch Hex (M, P) **Coming Soon**  
Large Chevron (M, P) **Coming Soon**

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

### RECOMMENDED USES

Commercial  
Residential  
\*Interior Floor  
\*\*Exterior Floor  
Interior Wall  
Exterior Cladding  
Fireplaces  
Shower Walls  
\*\*\*Shower Floors  
Steam Showers  
Pool & Spa  
\*Excludes 24 x 48 Rigato, wall only item  
\*\*24 x 48 R11 Anti-Slip Finish Only  
\*\*\*Matte 2 x 2 Mosaic Mesh, Matte 4 Inch Hex and 24 x 48 R11 Anti-Slip Finish Only

### STOCKED TRIM

3 x 12 SBN (M, P) **Coming Soon**

**DYNAMIC C.O.F. WET:** ≥0.42 (M)

**P.E.I. RATING:** 4 (P), 5 (M, R11)

**FROSTPROOF:** Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Invictus series is an Italian-made rectified color body porcelain. Created using digital print technology, the Invictus porcelain tile design resembles a vein cut travertine. You have several finish options with the desirable 24 x 48 large format tile size including matte, polished, R11 Anti-Slip Finish for exterior flooring as well as a decorative Rigato that offers a textural element to your space. The Rigato has a unique texture, similar to a combed surface. This series is suitable for residential and commercial applications. Because this material is a porcelain product, minimal maintenance is required.

There can be noticeable variances between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected.

Grout release is recommended for the polished finish, prior to grouting so grout powders do not fill pores in the tile surface, which can attract dirt when walked upon. It is recommended to use a coordinating grout color for all polished porcelain, contrasting grout colors are not recommended. For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS  
>20%PRE-CONSUMER  
RECYCLED CONTENT**

For packaging information, please contact your local Arizona Tile.

*DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.*

Please view actual material when making your selection, as the images on this page are only representative.

Revised 08/06/24