



Marvel Statuario Supremo Matte & Marvel Fior Di Bosco Matte



Marvel Black Atlantis



Marvel Calacatta Apuano



Marvel Calacatta Extra



Marvel Calacatta Prestigio



Marvel Fior Di Bosco



Marvel Statuario Supremo

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
≥20% PRE-CONSUMER
RECYCLED CONTENT**

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 11/08/24

MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Marvel Black Atlantis
Marvel Calacatta Apuano
Marvel Calacatta Extra
Marvel Calacatta Prestigio
Marvel Fior Di Bosco
Marvel Statuario Supremo

STOCKED FINISHES

Matte (M)
Polished (P)

STOCKED SIZES

12 × 24 (M, P)
24 × 24 (M, P)
24 × 48 (M, P)
2 × 2 Mosaic Mesh (M)
Archer Mesh (M, P)
Puzzle Mesh (M)
Small Hex 2-5/8 Mesh (M)
Straight Stack 1 × 12 Mesh (M)

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
*Shower Floors
Steam Showers
Pool & Spa
*2 × 2 Mosaic Mesh, Small Hex 2-5/8 Mesh, Puzzle Mesh and Straight Stack 1 × 12 Mesh Only

STOCKED TRIMS

3 × 12 SBN (M, P)
½ × 12 Pencil Bullnose (M, P)

D.C.O.F. WET: ≥0.42

P.E.I. RATING: n/a

FROSTPROOF: Yes

Marvel is a rectified color body porcelain tile which is inspired by the prestige of the most precious marbles of Italian tradition. Thanks to the surprising realism of pure colors, natural veins, intense shades and transparent clouding, each marble of reference is faithfully reproduced, adding all the benefits of porcelain tiles. This series is suitable for residential and commercial applications.

Because this material is a porcelain product, minimal maintenance is required. Grout release is recommended for the polished finish, prior to grouting so grout powders do not fill pores in the tile surface, which can attract dirt when walked upon. It is recommended to use a coordinating grout color for all polished porcelain, contrasting grout colors are not recommended. There can be noticeable variances between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular and square shape tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.