




Oro Gate



Oro Gate




Oro Gate



2 x 2 Mosaic Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



MADE IN ITALY

PRODUCT TYPE

Rectified Glazed Porcelain
Digital Print Technology

STOCKED COLOR

Oro Gate

STOCKED FINISHES

Matte

R11 Anti-Slip Finish

STOCKED SIZES

24 x 36

*24 x 36 R11 Anti-Slip Finish

2 x 2 Mosaic Mesh

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

RECOMMENDED USES

- Commercial
- Residential
- Interior Floor
- *Exterior Floor
- Interior Wall
- Exterior Cladding
- Fireplaces
- Shower Walls
- **Shower Floors
- Steam Showers
- Pool & Spa

* 24 x 36 R11 Anti-Slip Finish Only

**2 x 2 Mosaic Mesh and 24 x 36 R11 Anti-Slip Finish Only

D.C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the matte finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

Oro Gate is a rectified glazed porcelain offered in both matte and R11 Anti-Slip Finishes. This porcelain tile offers a lot of variation to mimic the quartzite natural stone this product is inspired by. Because this material is a porcelain product, minimal maintenance is required. There will be noticeable variances in color and movement between pieces. Therefore, it is important and recommended that a range of this product be viewed before finalizing a purchase.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. This series is suitable for residential and commercial applications.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.