# ARIZONA TILE

## PERLA SERIES





Perla Blanc



Perla Taj



Perla Blanc



Perla Taj



When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



# MADE IN ITALY

### PRODUCT TYPE

Rectified Color Body Porcelain Digital Print Technology

#### STOCKED COLORS

Perla Blanc Perla Tai

#### STOCKED FINISHES

R11 Anti-Slip Finish

#### STOCKED SIZES

 $12 \times 24$ 

 $24 \times 48$ 

\*24 × 48 R11 Anti-Slip Finish

2 × 2 Mosaic Mesh Coming Soon

### STOCKED TRIM

 $3 \times 12$  SBN Coming Soon

 $^{\star}\text{Continue}$  your indoor tile to your exterior living spaces with the R11 Anti-Slip Finish (available in all colors). To be certified as R11 Anti-Slip, a tile must pass an internationally recognized analysis showing that a person can maintain balance while standing on the wet tile at an incline of up to 27 degrees.

DCOF rating is a measurement of a tile's frictional resistance. The listed result is for the Standard Finish. The testing for R1 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing

#### **RECOMMENDED USES**

Commercial

Residential

\*Exterior Floor

Interior Floor

Interior Wall

Exterior Cladding

**Fireplaces** 

**Shower Walls** 

\*\*Shower Floors

Steam Showers

Pool & Spa

\*24 × 48 R11 Anti-Slip Finish Only \*\* $2 \times 2$  Mosaic Mesh &  $24 \times 48$  R11 Anti-Slip Finish Only

**DYNAMIC C.O.F. WET**: ≥0.42

P.E.I RATING: 4 FROSTPROOF: Yes

PRODUCT CONTAINS ≥40% PRE-CONSUMER RECYCLED CONTENT

Perla series is an Italian made color body porcelain which is inspired by vein cut natural stone. The soft neutral colors provide a beautiful, organic design aesthetic to any project.

Because this material is a porcelain product, minimal maintenance is required. There can be noticeable variances between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

For packaging information, please contact your local Arizona Tile.

Coming

Soon

2 × 2 Mosaic Mesh

2 × 2 Mosaic Mesh