



Aequa Nix



Aequa Castor



Hex 2-1/2



Aequa Cirrus



Hex 2-1/2



Aequa Nix



Hex 2-1/2



Aequa Silva



Hex 2-1/2



Aequa Tur



Hex 2-1/2

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Aequa Castor
Aequa Cirrus
Aequa Nix
Aequa Silva
Aequa Tur

STOCKED SIZES

8 × 32
*8 × 32 R11 Anti-Slip Finish
12 × 48
Hex 2-1/2 × 2-1/2

STOCKED TRIM

4 × 32 SBN

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

SPECIAL ORDER

Special Order Sizes and Finishes Available:
Please contact your Sales Representative for more details.

The Aequa Series is a rectified color body porcelain that is available in two finishes, including the R11 Anti-Slip Finish. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of a reclaimed wood, this series provides the warmth of timeworn matter that has taken on new colors and nuances over time. Because this material is a porcelain product, minimal maintenance is required. Aequa Series is stocked in two sizes, 8 × 32 and 12 × 48. The 8 × 32 size is also available in R11 Anti-Slip finish, which makes it ideal for exterior applications. All sizes and finishes are available in five colors. Numerous patterns can be created with the available sizes.

Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

RECOMMENDED USES

Commercial
Residential
Interior Floor
*Exterior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
Steam Showers
**Shower Floors
Pool & Spa

*R11 Anti-Slip Finish Recommended
**R11 Anti-Slip Finish and Hex 2-1/2 Inch Mosaic Only

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.