



Aequa Nix



Aequa Castor



Hex 2-1/2



Aequa Cirrus



Hex 2-1/2



Aequa Nix



Hex 2-1/2



Aequa Silva



Hex 2-1/2



Aequa Tur



Hex 2-1/2

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



## MADE IN ITALY

### PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

### STOCKED COLORS

Aequa Castor  
Aequa Cirrus  
Aequa Nix  
Aequa Silva  
Aequa Tur

### STOCKED SIZES

8 × 32 × 10mm  
\*8 × 32 × 10mm R11 Anti-Slip Finish  
12 × 48 × 10mm  
Hex 2-1/2 × 2-1/2 × 10mm

### STOCKED TRIM

4 × 32 × 10mm SBN

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

### SPECIAL ORDER

Special Order Sizes and Finishes Available:  
Please contact your Sales Representative for more details.

### RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
\*Exterior Floor  
Interior Wall  
Exterior Cladding  
Fireplaces  
Shower Walls  
Steam Showers  
\*\*Shower Floors  
Pool & Spa (waterline)

\*R11 Anti-Slip Finish Recommended  
\*\*R11 Anti-Slip Finish and Hex 2-1/2 Inch Mosaic Only

**DYNAMIC C.O.F. WET:** ≥0.42

**P.E.I. RATING:** 4

**FROSTPROOF:** Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Aequa Series is a rectified color body porcelain that is available in two finishes, including the R11 Anti-Slip Finish. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of a reclaimed wood, this series provides the warmth of timeworn matter that has taken on new colors and nuances over time. Because this material is a porcelain product, minimal maintenance is required. Aequa Series is stocked in two sizes, 8 × 32 × 10mm and 12 × 48 × 10mm. The 8 × 32 × 10mm size is also available in R11 Anti-Slip finish, which makes it ideal for exterior applications. All sizes and finishes are available in five colors. Numerous patterns can be created with the available sizes. Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
8 × 32 × 10mm	1.7216	6	10.3296	54	557.7984
8 × 32 × 10mm R11 Anti-Slip	1.7216	6	10.3296	54	557.7984
12 × 48 × 10mm	3.8736	4	15.4944	18	278.8992
Hex 2-1/2 × 2-1/2 × 10mm	0.82	10	8.2	45	369
4 × 32 × 10mm Surface Bullnose (SBN)	N/A	4	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.