

ARIZONA TILE

CEMENTO RASATO SERIES



Cemento Rasato Bianco

Cemento Rasato Antracite



12 x 24



2 x 2 Mosaic Mesh

Cemento Rasato Beige



12 x 24



2 x 2 Mosaic Mesh

Cemento Rasato Bianco



12 x 24



2 x 2 Mosaic Mesh

Cemento Rasato Grigio



12 x 24



2 x 2 Mosaic Mesh

MADE IN ITALY

PRODUCT TYPE

Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Cemento Rasato Antracite
Cemento Rasato Beige
Cemento Rasato Bianco
Cemento Rasato Grigio

STOCKED SIZES

12 x 24 x 9.4mm
2 x 2 x 9.4mm Mosaic Mesh

STOCKED TRIM

3 x 12 x 9.4mm SBN

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
*Shower Floors
Steam Showers
Pool & Spa
*2 x 2 Mosaic only

SPECIAL ORDER

Special Order Sizes and Finishes Available:
Please contact your Sales Representative for more details.

DYNAMIC C.O.F. WET: ≥ 0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

The Cemento Rasato Series is a color body porcelain that emulates a concrete appearance. It provides a clean, modern look to any environment.

When mixing sizes within a series, shade, texture and calibration differences should be expected. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial applications.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of the tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 x 24 x 9.4mm	2.0014	6	12.0084	48	576.4032
2 x 2 x 9.4mm Mosaic Mesh	0.9588	10	9.588	45	431.46
3 x 12 x 9.4mm Surface Bullnose (SBN)	N/A	30	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.

www.arizonatiles.com