



Club Grey



Club Beige



Club Grey



Club Tobacco



Club White



MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Club Beige
Club Grey
Club Tobacco
Club White

STOCKED SIZES

6 × 24 × 10mm
6-1/2 × 40 × 10mm

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
Steam Showers
Pool & Spa (waterline)

DYNAMIC C.O.F. WET: ≥ 0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

**PRODUCT CONTAINS
≥40% PRE-CONSUMER
RECYCLED CONTENT**

The Club Series is a rectified color body porcelain. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of a reclaimed, painted barn wood, this series provides the warmth of timeworn matter that has taken on new colors and nuances over time. Because this material is a porcelain product, minimal maintenance is required. Club Series is available in two sizes, 6 × 24 × 10mm and 6-1/2 × 40 × 10mm. It is available in four colors. Numerous patterns can be created with the available sizes. Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
6 × 24 × 10mm	0.9684	12	11.6208	40	464.832
6-1/2 × 40 × 10mm	1.7754	6	10.6524	48	511.3152

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.