

# ARIZONA TILE


# GIOIA SERIES



Gioia Greige



Gioia Rosso



Gioia Milk



Gioia Papaya



Gioia Bone



Gioia Mango



Gioia Greige



Gioia Lime



Gioia Ash



Gioia Avocado



Gioia Steel



Gioia Sky



Gioia Lava



Gioia Azure



Gioia Aqua



Gioia Navy



Gioia Turquoise

## MADE IN ITALY

### PRODUCT TYPE

Low-Fired Porcelain Wall Tile

### STOCKED COLORS

- Gioia Aqua
- Gioia Ash
- Gioia Avocado
- Gioia Azure
- Gioia Bone
- Gioia Greige
- Gioia Lava
- Gioia Lime
- Gioia Mango
- Gioia Milk
- Gioia Navy
- Gioia Papaya
- Gioia Rosso
- Gioia Sky
- Gioia Steel
- Gioia Turquoise

### RECOMMENDED USES

- Commercial
- Residential
- Interior Wall
- Exterior Cladding
- Fireplaces
- Shower Walls
- Steam Showers
- \*Pool & Spa (waterline)
- \*Not Recommended for Avocado color

### STOCKED SIZE

4 × 16 × 9mm

### STOCKED TRIM

3/8 × 8 × 9mm Pencil Bullnose

### SPECIAL ORDER

Special Order Sizes and Finishes Available:  
Please contact your Sales Representative for more details.

**DYNAMIC C.O.F. WET:** N/A

**FROSTPROOF:** Yes

The Gioia Series is a low-fired porcelain product. With bright colors and an undulated texture, this series is a beautiful accent to any design ranging from traditional to ultra modern. Because this material is a porcelain product, minimal maintenance is required. Gioia Series is available in 4 × 16 planks and sixteen colors.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
4 × 16 × 9mm	0.4304	24	10.3296	80	826.3680
3/8 × 8 × 9mm Pencil Bullnose	N/A	200	N/A	N/A	N/A

*DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.*

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.