# ARIZONA TILE

## PAROS SERIES



Paros 12 × 12 Black & White

Paros Black Hex Hex  $12 \times 24$  $12 \times 12$  $14 \times 16$  $8 - 1/2 \times 10$ Paros Navy  $12 \times 24$  $12 \times 12$ Hex Hex  $14 \times 16$  $8 - 1/2 \times 10$ Paros White  $12 \times 24$ 12 × 12 Hex Hex  $8-1/2 \times 10$  $14 \times 16$ 

## MADE IN ITALY

**PRODUCT TYPE** Color Body Porcelain

STOCKED COLORS Paros Black Paros Navy Paros White

### STOCKED SIZES

 $12 \times 12 \times 10 \text{mm} \text{ (Rectified)}$   $12 \times 24 \times 10 \text{mm} \text{ (Rectified)}$ Hex 8-1/2 × 10 × 10 mm (Pressed)
Hex 14 × 16 × 10 mm (Pressed)
2 × 2 × 10 mm Mosaic Mesh

PRODUCT CONTAINS

≥20% POST-CONSUMER

STOCKED TRIM 3 × 12 × 10mm SBN

#### **RECOMMENDED USES**

Commercial Residential Interior Floor Interior Wall Exterior Cladding Fireplaces Shower Walls \*Shower Floors Steam Showers Pool & Spa \*2 × 2 Mosaic Mesh Only

D.C.O.F. WET: ≥0.42 P.E.I. RATING: 4 FROSTPROOF: Yes

Paros is an Italian made porcelain tile. This line offers a square and rectangle field tile plus two sizes of hex tiles and a 2 × 2 mosaic mesh available in three bold yet universal colors. Unleash your creativity with all of the design possibilities! Because this material is a porcelain product, minimal maintenance is required. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

> When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.

	≤33% OFFSET		

		RECY	CLED CONTENT		
SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 × 12 × 10mm	0.9684	6	5.8104	96	557.7984
12 × 24 × 10mm	1.9368	6	11.6208	40	464.8320
Hex 8-1/2 × 10 × 10mm	0.4424	9	3.9816	72	286.6752
Hex 14 × 16 × 10mm	1.1190	9	10.071	48	483.4080
$2 \times 2 \times 10$ mm Mosaic Mesh	0.9588	10	9.588	45	431.46
$3 \times 12 \times 10$ mm Surface Bullnose (SBN)	N/A	30	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application. Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative

www.arizonatile.com