



Pietra Italia Beige 24 × 48 R11 Anti-Slip Finish

Pietra Italia White



12 × 24



2 × 2 Mosaic



Beige/White Stack

Pietra Italia Beige



12 × 24



2 × 2 Mosaic

Pietra Italia Grey



12 × 24



2 × 2 Mosaic



Black/Grey Stack

Pietra Italia Black




12 × 24



2 × 2 Mosaic

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
≥40% POST-CONSUMER
RECYCLED CONTENT**

MADE IN ITALY

PRODUCT TYPE

Rectified Through Body Porcelain

STOCKED COLORS

Pietra Italia Beige
Pietra Italia Black
Pietra Italia Grey
Pietra Italia White

STOCKED SIZES

12 × 24 × 10mm
*12 × 24 × 10mm R11 Anti-Slip Finish
24 × 24 × 10mm
24 × 48 × 10mm
*24 × 48 × 10mm R11 Anti-Slip Finish
Beige/White Stack
Black/Grey Stack

2 × 2 × 10mm Mosaic Mesh

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

STOCKED TRIM

3 × 12 × 10mm SBN

RECOMMENDED USES

Commercial
Residential
Interior Floor
*Exterior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
Steam Showers
**Shower Floors

Pool & Spa (waterline)

*R11 Anti-Slip Finish
** R11 Anti-Slip Finish, 2 × 2 Mosaic Mesh and Stacks Only

SPECIAL ORDER

Special Order Sizes, Colors and Finishes Available: Please contact your Sales Representative for more details.

D.C.O.F. WET: ≥ 0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

Pietra Italia is a rectified through body porcelain that emulates a limestone. It's available in two finishes, standard and R11 Anti-Slip Finish and provides a clean, natural stone look to any environment. Because this material is a porcelain product, minimal maintenance is required.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

SIZE	SF/PIECE	PIECES/BOX	SF/BOX	BOXES/PALLET	SF/PALLET
12 × 24 × 10mm	1.9368	8	15.4944	32	495.8208
12 × 24 × 10mm R11 Anti-Slip Finish	1.9368	8	15.4944	32	495.8208
24 × 24 × 10mm	3.8736	4	15.4944	32	495.8208
24 × 48 × 10mm	7.7472	2	15.4944	36	557.7984
24 × 48 × 10mm R11 Anti-Slip Finish	7.7472	2	15.4944	36	557.7984
Beige/White Stack & Black/Grey Stack	0.93 sq ft/sheet	N/A	N/A	N/A	N/A
2 × 2 × 10mm Mosaic Mesh	0.9588	10 sheets	9.588	45	431.46
3 × 12 × 10mm Surface Bullnose (SBN)	N/A	30	N/A	N/A	N/A

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Standard packaging quantities are noted above, but variances may occur.

Please view actual material when making your selection, as the images on this page are only representative.