

ARIZONA TILE

THEMAR SERIES




Themar Bianco Lasa

Themar Bianco Lasa



12 x 24




2 x 2



Hex 2-3/8

Themar Crema Marfil



12 x 24



2 x 2



Hex 2-3/8

Themar Grigio Savoia



12 x 24



2 x 2



Hex 2-3/8

Themar Statuario V



12 x 24



2 x 2



Hex 2-3/8

Themar Venato Gold



12 x 24



2 x 2



Hex 2-3/8

MADE IN ITALY

PRODUCT TYPE

Rectified Glazed Porcelain
Digital Print Technology

STOCKED COLORS

Themar Bianco Lasa
Themar Crema Marfil
Themar Grigio Savoia
Themar Statuario V
Themar Venato Gold

STOCKED FINISHES

Matte
Polished

STOCKED SIZES

3 x 12
12 x 24
24 x 24
2 x 2 Mosaic Mesh
Hex 2-3/8 x 2-3/8 Mesh

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
**Shower Floors
Steam Showers
Pool & Spa

**Matte 2 x 2 Mosaic and Hex 2-3/8 Only

STOCKED TRIM

1/2 x 11-5/8 Pencil Bullnose
3 x 12 SBN

SPECIAL ORDER

Special Order Sizes, Colors and Finishes
Available: Please contact your Sales Representative for more details.

D.C.O.F. WET: ≥0.42 (matte)

P.E.I. RATING: 5 (matte)

4 (polished)


FROSTPROOF: Yes

The Themar Series is a rectified glazed porcelain. Digital print technology creates some of the same characteristics as some of the most sought-after natural stones, including marble. Because this material is a porcelain product, maintenance risks involved with actual stone are eliminated. There will be noticeable variations in color and movement between pieces. Therefore, it is important and recommended that a range of this product be viewed before finalizing a purchase.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. This series is suitable for residential and commercial applications.

It is recommended to use a coordinating grout color for all polished porcelain, contrasting grout colors are not recommended. For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length longer than 15 inches and rectangular shape and plank tile, per industry standard. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
20% PRE-CONSUMER
RECYCLED CONTENT**

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 05/03/24

www.arizonatile.com