ARIZONA TILE

TRU MARMI SERIES



Tru Marmi Extra



Tru Marmi Arabescato





4 Inch Hex Mesh



Tru Marmi Extra



Tru Marmi Gold



Tru Marmi Silver



Tru Marmi Venatino



2 × 2 Mosaic Mesh



2 × 2 Mosaic Mesh

4 Inch Hex Mesh

4 Inch Hex Mesh



2 × 2 Mosaic Mesh



2 × 2 Mosaic



2 × 2 Mosaic Mesh



4 Inch Hex Mesh

4 Inch Hex Mesh

MADE IN ITALY

PRODUCT TYPE

Rectified Glazed Porcelain Digital Print Technology

STOCKED COLORS

Tru Marmi Arabescato Tru Marmi Extra Tru Marmi Gold Tru Marmi Silver Tru Marmi Venatino

STOCKED FINISHES

Matte (M) Polished (P)

STOCKED SIZES

12 × 24 (M & P) 24 × 48 (M & P) 4 Inch Hex Mesh (M) 2 × 2 Mosaic Mesh (M)

RECOMMENDED USES

Commercial Residential Interior Floor

Interior Wall

Exterior Cladding

Fireplaces

Shower Walls

*Shower Floors

Steam Showers

Pool & Spa

 $^{*2} \times ^{2}$ Matte Mosaic Mesh and 4 Inch Hex Mesh

STOCKED TRIM

1/2 × 11-5/8 Pencil Bullnose (M & P) 3 × 12 Surface Bullnose (M & P)

SPECIAL ORDER

Special Order Sizes, Colors and Finishes Available: Please contact your Sales Representative for more details

D.C.O.F. WET: ≥0.42 (matte)

P.E.I. RATING: 4 **FROSTPROOF**: Yes

The Tru Marmi Series is a rectified glazed porcelain. Digital print technology creates some of the same characteristics as some of the most sought-after natural stones, including marble. Because this material is a porcelain product, maintenance risks involved with actual stone are eliminated. There will be noticeable variations in color and movement between pieces. Therefore, it is important and recommended that a range of this product be viewed before finalizing a purchase.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. This series is suitable for residential and commercial applications.

It is recommended to use a coordinating grout color for all polished porcelain, contrasting grout colors are not recommended. For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

> When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise

specified by the	manuracture	r.	
≤33% OFFSET			