



More Wood Grigio R11 Anti-Slip Finish



More Wood Ciliegio



More Wood Grigio



More Wood Miele



More Wood Noce

## MADE IN ITALY

### PRODUCT TYPE

Rectified Color Body Porcelain  
Digital Print Technology

### STOCKED COLORS

More Wood Ciliegio  
More Wood Grigio  
More Wood Miele  
More Wood Noce

### STOCKED SIZES

8 × 32  
\*8 × 32 R11 Anti-Slip Finish  
8 × 48

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

### SPECIAL ORDER

Special Order Sizes, Colors and Finishes Available: Please contact your Sales Representative for more details.

### RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
\*Exterior Floor  
Interior Wall  
Exterior Cladding  
Fireplaces  
Shower Walls  
\*Shower Floors  
Steam Showers  
Pool & Spa  
\* R11 Anti-Slip Finish Only

**DYNAMIC C.O.F. WET:** ≥0.42

**P.E.I. RATING:** 4

**FROSTPROOF:** Yes


DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The More Wood Series is a rectified color body porcelain that is available in two finishes, including the R11 Anti-Slip Finish. It is the synthesis of digital technology applied to aesthetic research. Giving the appearance of natural wood, this series provides warmth to any space. More Wood Series is available in two sizes, 8 × 32 and 8 × 48 and it is available in four colors. Because this material is a porcelain product, minimal maintenance is required.

Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



*DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.*

Please view actual material when making your selection, as the images on this page are only representative.

Revised 05/01/24