



Pietra Italia Beige 24 x 48



Pietra Italia White



2 x 2
Mosaic Mesh



Beige/White
Stack



Pietra Italia Beige



2 x 2
Mosaic Mesh



Pietra Italia Grey



2 x 2
Mosaic Mesh



Black/Grey
Stack



Pietra Italia Black



2 x 2
Mosaic Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
≥40% POST-CONSUMER
RECYCLED CONTENT**

MADE IN ITALY

PRODUCT TYPE

Rectified Through Body Porcelain

STOCKED COLORS

Pietra Italia Beige

Pietra Italia Black

Pietra Italia Grey

Pietra Italia White

STOCKED SIZES

12 x 24

*12 x 24 R11 Anti-Slip Finish

24 x 24

24 x 48

*24 x 48 R11 Anti-Slip Finish

Beige/White Stack

Black/Grey Stack

2 x 2 Mosaic Mesh

STOCKED TRIM

3 x 12 SBN

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

RECOMMENDED USES

Commercial

Residential

Interior Floor

*Exterior Floor

Interior Wall

Exterior Cladding

Fireplaces

Shower Walls

Steam Showers

**Shower Floors

Pool & Spa

*R11 Anti-Slip Finish Only

** R11 Anti-Slip Finish, 2 x 2 Mosaic Mesh and Stacks Only

SPECIAL ORDER

Special Order Sizes, Colors and Finishes Available: Please contact your Sales Representative for more details.

DYNAMIC C.O.F. WET: ≥ 0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

Pietra Italia is a rectified through body porcelain that emulates a limestone. It's available in two finishes, matte and R11 Anti-Slip Finish and provides a clean, natural stone look to any environment. Because this material is a porcelain product, minimal maintenance is required.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 05/03/24